

LSP 14500-20F

Hybrid Primary Li-SOCl₂ battery

3.6 V AA size bobbin cell fitted with a 20F LIC

Saft's LSP 14500-20F battery is ideally suited for long life applications featuring low base currents and periodic pulses and periodic high current pulses up to 1.5 A.

Benefits

- High pulse capability.
- High voltage response, stable even after long dormant periods.
- Low self-discharge compatible with long operating life (less than 1.5% after 1 year of storage at +20 °C).
- Wide operating temperature range (-20°C to +70°C).
- Easy integration into systems.

Key features


- Battery made of Saft's LS 14500 AA size bobbin Li-SOCl₂ cell fitted with a 20 F LIC (Lithium Ion Capacitor) in parallel connection for pulse support.
- Well controlled passivation.
- The cell contains a non-flammable electrolyte.
- Manufactured in the EU.

Designed to meet all major quality, safety and environmental standards

- Safety: UL 1642, IEC 60086-4 (at cell level)
- Transport: UN 3090, 3091 & 3499 for components and tested to UN 38.3.
- Quality: ISO 9001, Saft World Class program.
- Environment: ISO 14001, RoHS and REACH compliant.

Typical applications

- Smart metering.
- Internet of Things.
- Tracking systems.
- Environmental monitoring.



Electrical characteristics ^[i]

Typical capacity (at 2 mA, +20°C, 2.0 V cut-off) ^[ii]	2.6 Ah
Open circuit voltage (at +20°C)	3.67 V
Nominal voltage (under 0.2mA, +20°C)	3.6 V
Nominal energy	9.36 Wh
Typical pulse capability ^[iii]	At 20°C 1.0 A / 3s pulses
Maximum recommended continuous current ^[iv]	50 mA

Operating conditions

Operating temperature range	-20°C to +70°C
Storage temperature recommended ^[v]	max +30°C

Physical characteristics (sleeved battery)

Length (max)	25.7 mm
Width (max)	15.2 mm
Height (max)	52.7 mm
Typical weight	22 g
Li metal content	(approx.) 0.7 g

References

Saft part number	60125F
Battery connector ^[vi]	JST (PHR-2)

[i] Typical values relative to cells stored up to one year at +30°C max.

[ii] Dependent upon current drain, temperature, cut-off and battery orientation.


[iii] For further details consult Saft.

[iv] Higher currents are possible, consult Saft.

[v] For more severe conditions, consult Saft.

[vi] Other terminations are available, consult Saft.

LSP 14500-20F




Storage

- The storage area should be clean, cool (preferably not exceeding +30°C), dry and ventilated.


Warning

- Fire, explosion and burn hazard.
- Do not recharge, short circuit, crush, disassemble, heat above 100°C (212°F), incinerate, or expose contents to water.
- Do not solder directly to the battery (use the connector).


LSP 14500-20F Maximum pulse width at various temperatures [3.6V to 2.8V]



LSP 14500-20F voltage during a pulse at 20°C



LSP 14500-20F voltage during a pulse at +55°C



Saft

26, Quai Charles Pasqua,
92300 Levallois Perret -France
Tel.: +33 (0)1 49 93 19 18
Fax: +33 (0)1 49 93 19 69
www.saftbatteries.com

Saft America, Inc

313 Crescent Street
Valdese, NC 28690, USA
Tel.: +1 (828) 874 41 11
Fax : +1 (828) 879 39 81
www.saftbatteries.com

Doc N°: 31204-2-0621

Edition: June 2021

Information in this document is subject to change without notice and becomes contractual only after written confirmation by Saft.

Published by the Communication Department

Photo credit: Saft

Produced by CE Marketing Department

